


Innova 60/65/75/85/100 B / M - 70 S



The innovative scrubbing machine which allows a dramatic reduction in the cost of cleaning

Available in the version with one 60 cm working width disc brush as well as in the version with two 65, 75, 85 and 100 cm disc brushes and in the version with 1 cylindrical brush with a working width of 69 cm



Innova 60 B is the highly user-friendly scrubbing machine suitable for maintenance cleaning of commercial surfaces up to 3000 sq.m



Innova 60 B is a battery ride-on scrubbing machine with automatic traction drive available in the version with 1 disc brush, with a working width of 61 cm.

Innova 60 B was designed in order to replace a walk-behind scrubbing machines, with the aim to drastically reduce sq.m scrubbed cost offering a real competitive advantage, particularly for the end user.

User-friendliness
WITHOUT ADDITIONAL COSTS
FOR OPERATOR TRAINING



Just turn the key to start working immediately



The brush head and the squeegee are lowered/raised by simply using two levers



Compared to a walk-behind scrubbing machine Innova 60 B offers the following benefits:

- · Advantageous purchase price,
- Economic advantage while using it.
 Extremely convenient to clean surfaces,
 starting from 1200 sq.m with at least two cleaning operations per week,
- The economic advantage to use it up to four non-stop working hours thanks to the optimization of energy consumption,
- Compact size which allows the machine to pass even through traditional doors or be transported in lifts.
- The advantage of performing even in highly noise-sensitive environments such as nursing homes and hospitals, thanks to its very low acoustic pressure level.





Innova 60 B

Innova 65/75/8

Innova 65/75/85/100 B / M - 70 S. Maximum equipment and maximum cost saving for maintenance cleaning costs of surfaces up to 3500 sq.m

Innova 65/75/85/100 B / M - 70 S is a battery rideon scrubbing machine with automatic traction drive, available in the scrubbing version with 2 disc brushes, with working width of 65, 75, 85 and 100 cm and in the sweeping version with 1 cylindrical brush of 69 cm.

Innova 65/75/85/100 B / M - 70 S is a scrubbing machine which guarantees a dramatic reduction in the cost of cleaning thanks to an advantageous purchase price and complete equipment of all Comac systems which reduce waste and consumption.

Compared to a walk-behind scrubbing machines Innova 65/75/85/100 B - 70 S offer the following benefits:

- No more operator training thanks to "Working program selector" equipped as standard (automatic version),
- Optimization of consumption thanks to the Start&Stop device equipped as standard which ensures a working autonomy increase up to 35% (compared to the previous model) so that the machine can be used for up to four non stop working hours (automatic version),
- Silence and energy saving thanks to Eco device (automatic version).

Thanks to Comac water and detergent dosing system (CDS, Comac Dosing System) solution (water and detergent) saving up to 50% is ensured






Separate management of water and detergent

Innova 65/75/85/100 B - 70 S machines are equipped with a CDS as well as a water distributor system which guarantees a uniform distribution of water on both brushes: even with reduced flow rates. In addition, Innova 65/75/85/100 B - 70 S machines are equipped with a START&STOP system which stops water flow and brushes when the machine is idle













Innova 65/75/85 is equipped as standard with a device that allows the adjustment of the working width from 65 to 85 cm.
(for further information, please contact Comac Technical Assistance Service)

Innova 100 B

Innova 70 S

cowo:

Innova 60/65/75/85/100 B / M - 70 S machines are safe, productive and user-friendly

Choose the working system that better meets your needs: manual or automatic!

Manual working system (M version)

In the manual version the squeegee and the brush head are controlled by two independent levers giving outstanding user-friendliness even when used by unskilled operators.

Innova M is available in the versions with 60, 65, 75, 85 and 100 cm working width.



Automatic working system

The automatic version is equipped with a working program selector making the use of the machine extremely intuitive. It allows to choose the selection of four pre-set working programs:

- 1. Transfer,
- 2. Drying,
- 3. Scrubbing/Drying,
- 4. Scrubbing only.

Once selected the most suitable program, Innova 65/75/85/100 B - 70 S does all the thinking.



NEW INSTRUMENT PANEL WITH "ECO" DEVICE



Reduces noise levels



Reduces energy consumption

The automatic version is equipped as standard with Eco device that guarantees a very low acoustic pressure level, allowing to perform in highly noise-sensitive environments such as nursing homes and hospitals, without disturbing the environment or the people who live in it








Automatic swing-in of the brush head when accidentally impacted (Innova 65/75/85/100 B / M)




Automatic squeegee uncoupling when accidentally impacted



Innova 60/65/75/85/100 B / M - 70 S is available on request with a support for your manual cleaning kit, that allows to complete the cleaning operation



Best manoeuvrability even in narrow spaces thanks to tight turning diameter





Low center of gravity for optimum stability. Capable of ramp gradients up to 18%











Easy rubber replacement without any tools on the exclusive Comac squeege (Patent Pending)

COMAC Spa reserves the right, at anytime, to make technical and/or equipment modifications without prior notification. The images are shown as reference only and are not binding as to the actual design and/or equipment. + AH - 02/17 - Copyright © COMAC 2011

0 0

Innova 60/65/75/85/100 B / M - 70 S available equipment

STANDARD EQUIPMENT	Innova 60 B 65/75/85/100 M	Innova 65/75/85/100 B	Innova 70 S	STANDA	ARD EQUIPMENT	6	Innova 60 B 5/75/85/100 M	Innova 65/75/85/100 B	Innova 70 S
Water and detergent management				Comfor	rt				
Water Management	•/-	-	-		d suction (Eco)		-	•	•
CDS (Comac Dosing System)	-	optional	optional	,	nitizable tanks		•	•	•
Water dispenser Eco ON/OFF	-/•	•	-	0	nme selector rough access		-	•	•
Start&Stop	•	•			rd battery charger		optional	optional	optional
Fast water filling with drip stop		•		Hour m	, ,		•	•	•
Water level indicator	•	•	•		charge level		•	•	•
					tank Fast Fill		-	optional	optional
Scrubbing performance		(Inc CE /7E /0E D)		Support	t kit of manual cleaning sy	/stems	optional	optional	optional
Adjustable brush pressure Ramp climbing capacity		(Innova 65/75/85 B)		Safety					
Squeegee with polyurethane		•	•		d and non-marking front of	drive wheel			
rubber bars usable on 4 sides					and non-marking rear wh				•
Variable scrubbing head	-/•	(Innova 65/75/85 B)	-		nical service and parking b	rakes	•	•	•
3-stage suction motor	-	optional	optional	Flasher	St. I. I. San	ľ	optional	optional	optional
Operating autonomy					ee with shock-resistant co ng head with impact-elicit		•	•	•
(4) 6V/210 Ah C5 batteries	optional	optional	optional		nan's switch	ca swinging in		•	•
(2) 12V/130 Ah C5 batteries	optional	optional	optional	Horn			•	•	•
TECHNICAL DATA		Innova 60B	Innova 6	55B/M	Innova 75B/M	Innova 85B/	M Innova 10	00B/M Inno	va 70S
Squeegee width	mm/inch	780/30	970/3	58,3	970/38,3	1085/43	1085/	43 108	35/43
Disc brushes Ø (n.)	mm/inch	610/24 (1)	340/13,	,4 (2)	390/15,4 (2)	430/17 (2)	508/20	(2)	-
Cylindrical brushes \varnothing (n.)	mm/inch	-	-		-	-	-	210x690/	8,3x27,2 (1)
Brush rpm	rpm	170	170)	170	170	120	5	520
Brush motor (n.)	V/W	24/450 (1)	24/450	(2)	24/450 (2)	24/450 (2)	24/600	(2) 24/5	60 (1)
Suction motor	V/W	24/310	24/3	10	24/310	24/310	24/3	10 24	/350
Traction motor	V/W	24/400	24/4	00	24/400	24/400	24/40	00 24	/400
Forward speed	km/h	0÷6	0÷(6	0÷6	0÷6	0÷6	5 0	ı÷6
Max gradient at full load	%	up to 18	up to	18	up to 18	up to 18	up to	18 up	to 18
Turning diameter	mm/inch	1910/75,4	1910/	75,4	1910/75,4	1910/75,4	1910/7	75,4 1910	0/75,4
Batteries (n.)	V/Ah C5	6/210 (4)	6/210	(4)	6/210 (4)	6/210 (4)	6/210	(4) 6/2	10 (4)
Batteries weight	kg/lb	136/300	136/3	300	136/300	136/300	136/3	00 136	5/300

cowoc	Working width mm/inch	Brushes pressure Kg/lb	Power supply V/ traction	Solution tank I/gal	Recovery tank I/gal	Working capacity up to sq.m/h/ft²/h	Machine dimensions mm/inch L x H x W	Machine weight kg/lb (without batteries)
Innova 60B	610/24	30/66,2	24/aut.	110/29	125/33	3660/39400	1495/59 1320/52 680/26,8	223/492
Innova 65B/ 65M	650/26	30÷60/30 66,2÷132,4/66,2	24/aut.	110/29	125/33	3900/42000	1495/59 1320/52 680/26,8	223/492
Innova 75B/ 75M	750/29,6	30÷60/30 66,2÷132,4/66,2	24/aut.	110/29	125/33	4500/48400	1495/59 1320/52 680/26,8	223/492
Innova 85B/ 85M	850/34	30÷60/30 66,2÷132,4/66,2	24/aut.	110/29	125/33	5100/54900	1495/59 1320/52 680/26,8	223/492
Innova 100B/ 100M	1000/40	45/99,3	24/aut.	110/29	125/33	6000/64600	1495/59 1320/52 1035/40,8	240/530
Innova 70S	690/27	20/44	24/aut.	110/29	125/33	4100/44100	1495/59 1320/52 805/31,8	233/514









COMAC spa Via Maestri del Lavoro, 13 37059 Santa Maria di Zevio - Verona - Italy Tel. +39 045 8774222 - Fax +39 045 8750303 on line: www.comac.it - e-mail: com@comac.it